

Tungsten Carbide End Mills UNIMAX Series

Vol.2

Barrel End Mills For Highly Efficient Finishing

UTCOAT 4 Flutes Oval Barrel Form

Add 2

COVB

Total 4 Models

UTCOAT 4 Flutes Standard Taper Barrel Form

Add 3

CSTB

Total 5 Models

UTCOAT 4 Flutes Wide Taper Barrel Form

NEW

CWTB

Total 2 Models





COVB

Super
MG

UT
COAT

Form
±0.01

Shank Dia
0/-0.005



Additional 2 Models

Material Applications (☆ Highly Recommended ◎ Recommended ○ Suggested)

Work Material															
CARBON STEELS S45C S55C	ALLOY STEELS SK / SCM SUS	PREHARDENED STEELS NAK HPM	HARDENED STEELS			CAST IRON	ALUMINUM ALLOYS	GRAPHITE	COPPER	PLASTICS	GLASS FILLED PLASTICS	TITANIUM ALLOYS	HEAT RESISTANT ALLOYS	CEMENTED CARBIDE	HARD BRITTLE (NON-METALLIC) MATERIALS
			~55HRC	~60HRC	~70HRC										
◎	◎	◎	◎			○	◎		◎			○	○		

Features

Broad range of application available with UTCOAT.
Suitable for narrow interference area with small inclined angle.



Total 4 models

Unit (mm)


Model Number	Tip R	Barrel R	Length of Cut l	Overall Length L	Shank Diameter $\varnothing d$	Price ¥
COVB 4020-85	R1	R85	19.2	60	6	23,400
COVB 4020-90		R90	23.9	70	8	29,000
COVB 4040-80	R2	R80	23.4	80	10	33,330
COVB 4040-80-12		R80	26.6	80	12	40,320

* Additional model

COVB Milling Conditions

WORK MATERIAL			ALUMINUM ALLOYS A7075				PREHARDENED STEELS PXA30 (30~45HRC)				HARDENED STEELS SKD61 / STAVAX (45~55HRC)			
Model Number	Tip R (mm)	Barrel R (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)
4020-85	R1	R85	10,500	2,400	2.85	0.1	4,700	1,070	2.4	0.1	3,800	900	1.9	0.07
4020-90		R90	9,250	2,200	3.6	0.1	4,250	980	2.9	0.1	3,500	850	2.4	0.07
4040-80	R2	R80	8,000	2,000	3.5	0.1	3,800	900	3	0.1	3,200	800	2.4	0.07
4040-80-12		R80	6,750	1,800	4	0.1	3,350	900	3.4	0.1	2,900	750	2.7	0.07

Note:
· Set spindle speed, feed rate, and axial depth (a_p) in accordance with the required surface quality.



a_p : Axial Depth (mm)
 a_e : Radial Depth (mm)



CSTB





Additional 3 Models

Material Applications (☆ Highly Recommended ◎ Recommended ○ Suggested)

Work Material															
CARBON STEELS S45C S55C	ALLOY STEELS SK / SCM SUS	PREHARDENED STEELS NAK HPM	HARDENED STEELS			CAST IRON	ALUMINUM ALLOYS	GRAPHITE	COPPER	PLASTICS	GLASS FILLED PLASTICS	TITANIUM ALLOYS	HEAT RESISTANT ALLOYS	CEMENTED CARBIDE	HARD BRITTLE (NON-METALLIC) MATERIALS
			~ 55HRC	~ 60HRC	~ 70HRC										
◎	◎	◎	◎			○	◎			◎		○	○		

Features

- Broad range of application available with UT COAT.
- Suitable for finishing on straight and inclined walls with larger barrel R.



Total 5 models

Unit (mm)


Model Number	Half Included Angle $\alpha / 2$	Tip R R1	Barrel R R2	Third R R3	Length of Cut l	Overall Length L	Shank Diameter $\varnothing d$	Price ¥
CSTB 4020-200-30	15°	R1	R200	R3	8.6	60	6	23,400
* CSTB 4030-250-40	20°	R1.5	R250	R4	8.7	70	8	29,000
* CSTB 4040-250-40	20°	R2	R250	R5	10.7	80	10	33,330
CSTB 4060-250-45	22.5°	R3	R250	R6	10.7	100	12	40,320
* CSTB 4020-200-85	42.5°	R1	R200	R1	6.4	100	12	40,320

* Additional model

CSTB Milling Conditions

WORK MATERIAL			ALUMINUM ALLOYS A7075				PREHARDENED STEELS PXA30 (30~45HRC)				HARDENED STEELS SKD61 / STAVAX (45~55HRC)			
Model Number	Tip R (mm)	Barrel R (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)
4020-200-30	R1	R200	18,000	2,400	2.85	0.1	11,500	1,800	1.9	0.075	9,000	1,440	1.5	0.075
4030-250-40	R1.5	R250	15,600	2,400	2.85	0.1	10,300	1,600	2.4	0.075	8,000	1,200	2	0.075
4040-250-40	R2	R250	13,200	2,400	2.85	0.1	9,100	1,600	2.4	0.075	7,000	1,200	2	0.075
4060-250-45	R3	R250	10,800	2,400	2.85	0.1	8,000	1,600	2.4	0.075	6,000	1,200	2	0.075
4020-200-85	R1	R200	10,800	1,200	2.85	0.1	8,000	700	2	0.075	6,000	500	2	0.05

- Note:
- Set spindle speed, feed rate, and axial depth (a_p) in accordance with the required surface quality.



a_p : Axial Depth (mm)
 a_e : Radial Depth (mm)

UTCOAT 4 Flute Wide Taper Barrel Form



CWTB

Super MG
UT COAT
Form ±0.01
Shank Dia 0/-0.005



NEW

Material Applications (☆ Highly Recommended ◎ Recommended ○ Suggested)

Work Material															
CARBON STEELS S45C S55C	ALLOY STEELS SK / SCM SUS	PREHARDENED STEELS NAK HPM	HARDENED STEELS			CAST IRON	ALUMINUM ALLOYS	GRAPHITE	COPPER	PLASTICS	GLASS FILLED PLASTICS	TITANIUM ALLOYS	HEAT RESISTANT ALLOYS	CEMENTED CARBIDE	HARD BRITTLE (NON-METALLIC) MATERIALS
			~55HRC	~60HRC	~70HRC										
◎	◎	◎	◎			○	◎		◎			○	○		

Features

Broad range of application available with UTCOAT.
Suitable for finishing on flat surface with wide taper angle.



Total 2 models

Unit (mm)


Model Number	Half Included Angle $\alpha/2$	Tip R R1	Barrel R R2	Third R R3	Length of Cut ℓ	Overall Length L	Shank Diameter $\varnothing d$	Price ¥
CWTB 4020-200-100	50°	R1	R200	R1	4.3	80	10	25,140
CWTB 4020-250-130	65°		R250		2.8			

CWTB Milling Conditions

WORK MATERIAL			ALUMINUM ALLOYS A7075				PREHARDENED STEELS PXA30 (30~45HRC)				HARDENED STEELS SKD61 / STAVAX (45~55HRC)			
Model Number	Tip R (mm)	Barrel R (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)	Spindle Speed (min ⁻¹)	Feed Rate (mm/min)	a_p Axial Depth (mm)	a_e Radial Depth (mm)
4020-200-100	R1	R200	20,000	5,000	0.2	4	12,000	2,400	0.1	4	9,000	1,100	0.075	4
4020-250-130		R250	20,000	5,000	0.1	2.5	12,000	2,400	0.1	2.5	9,000	1,100	0.075	2.5

Note:

· Set spindle speed, feed rate, and radial depth (a_e) in accordance with the required surface quality.



a_p : Axial Depth (mm)


a_e : Radial Depth (mm)



Milling Video



Standard Ball End Mills



Larger a_p

Barrel End Mills



The challenge is to mill with 'Super' efficiency on a 5-axis machine!

Size 77 × 130 × Height 80 mm

MC Mikron MILL S 400 U (GF Machining Solutions)

CAD/CAM hyperMILL (OPEN MIND Technologies)

Start!

Whole area Roughing



5 Flute Radius
CXRS Ø10 x CR2
n : 7,040 min⁻¹
Vf : 4,600 mm/min
 a_p : 20 mm a_e : 0.25 mm
5-axis + trochoidal high speed roughing!

Outer curved wall finishing
Large R corner finishing



4 Flute Standard Taper Barrel
CSTB R3 x R250 x Ø12
n : 8,000 min⁻¹
Vf : 400 mm/min
 a_p : 0.8/1.2 mm a_e : 0.075 mm
Wide-pitch finishing with the barrel end mill!

Small R corner finishing



3 Flute Long Neck Ball
CFLB R1.5 x L10
n : 24,000 min⁻¹
Vf : 1,500 mm/min
 a_p : 0.3 mm a_e : 0.1 mm

Flute part Roughing



4 Flute Radius
CXERS Ø 8 x CR2
n : 3,600 min⁻¹
Vf : 900 mm/min
 a_p : 20 mm a_e : 0.8 mm

Small R corner finishing



4 Flute Standard Taper Barrel
CSTB R1 x R200 x Ø6
n : 11,500 min⁻¹
Vf : 900 mm/min
 a_p : 0.05 mm a_e : 0.07 mm
Smooth processing of uneven curved surfaces

Whole area Semi-Roughing



3 Flute Ball
CFB R3
n : 12,000 min⁻¹
Vf : 2,000 mm/min
 a_p : 0.6 mm a_e : 1.8 mm
Removal of uneven surfaces after roughing using high feed rate!

Inner curved wall finishing



4 Flute Standard Taper Barrel
CSTB R1 x R200 x Ø6
n : 11,500 min⁻¹
Vf : 900 mm/min
 a_p : 0.375/0.75 mm a_e : 0.075 mm
Cornering at the tip R of the barrel end mill reduces the number of tools and the inconvenience of tool change!

Finish!



Advisory for Safe Use of UNIMAX Tungsten Carbide End Mills

Correct application and operation is strongly advised to avoid clogging, abrasion, etc, that could cause serious accidents or injuries. Ignition or sparks generated during milling could lead to fire or extreme damage to the work piece. End Mills are made with very sharp cutting edges and must be handled with extra care.

- * Never touch the cutting edge with your bare hands, as this could cause serious injury. Special caution is required when opening the package.
- * Dropping the tool could cause breakage or flying debris, leading to serious injury.
- * During milling, unexpected impact or shock on the tool could cause breakage or flying debris. Ensure to use protective items such as safety glasses and a face guard.
- * For best results, fine parameter adjustment may be required, depending on the materials; milling shape and strategy; machine rigidity and spindle capability.
- * Use a machine that has high rigidity and generates a low level of vibration.
- * Do not use flammable cutting oils.

Advisory for regrinding UNIMAX Tungsten Carbide End Mills

- * Never regrind the tool without wearing safety glasses and a face guard.



UNION TOOL CO.

U.S. UNION TOOL, INC.

(U.S. HEADQUARTERS)
1260 N. Fee Ana Street, Anaheim, CA 92807-1817 U.S.A.
Tel: 1-714-521-6242 Fax: 1-714-521-8642

NORTHERN CALIFORNIA REGIONAL SERVICE CENTER

(Customer Service, Santa Clara, California)
1805 Little Orchard Street, Suite 120, San Jose, CA 95125 U.S.A.
Tel: 1-408-982-0205 Fax: 1-408-982-0320

UPPER MIDWEST REGIONAL SERVICE CENTER

(Customer Service, Minneapolis, Minnesota)
155 Bridgepoint Drive, Unit 3 South St. Paul, MN 55075 U.S.A.
Tel: 1-651-552-0440 Fax: 1-651-552-0435

TAIWAN UNION TOOL CORP.

No.180, Zhong-Zun Street., 14 Neighborhood, Bin-Hai Vil.,
Lu-Zhu Dist., Taoyuan City, 338 TAIWAN
Tel: 886-3-354-3111 Fax: 886-3-354-3110

UNION TOOL EUROPE S.A.

Avenue des Champs-Montants 14aCH-2074 Marin /
Neuchatel SWITZERLAND
Tel: 41-32-756-6633 Fax: 41-32-756-6634

UNION TOOL (SHANGHAI) Co., LTD.

No.9-10, Lane 385, Gaoji Road, Sijing High New Technology
Development Zone, Songjiang District, Shanghai, 201601 CHINA
Tel: 86-21-5762-8577 Fax: 86-21-5762-8436

UNION TOOL HONG KONG LTD.

Rm 503, 5/F, Win Century Centre, 2A Mong Kok Rd, Mong Kok,
Kowloon, HONG KONG
Tel: 852-2370-3012 Fax: 852-2370-2111

DONGGUAN UNION TOOL LTD.

YingHua TaiYing Industry Park, Hongmei Town,
Dongguan City, Guangdong, 523160 CHINA
Tel: 86-769-8884-8900 Tel: 86-769-8884-8901
Fax: 86-769-8884-8296

UNION TOOL SINGAPORE PTE LTD.

No.31 Harrison Road, #05-01, SINGAPORE 369649
Tel: 65-6846-9309 Fax: 65-6846-0197

UNION TOOL (THAILAND) CO., LTD.

No.55/73 Moo 15 Bangsaotong Sub-District, Bangsaotong District,
Samutprakarn 10570 THAILAND
Tel: 66-2-130-0908 Fax: 66-2-130-0909



0120-60-2620

<https://www.uniontool.co.jp>

Price & Specifications are subject to change without notice.

2021.03 VEM2 RG 5.5KA

**PRODUCT
NEWS**

PN-E-003

SERIES EXPANSION

 **DIJET®**

5-AXIS SERIES

Newly developed "barrel" and "torus" geometry
for live 5-AXIS finishing









DIJET GmbH

www.dijet.de

Style & Machining area for 3-Axis machine

Features

<p>MQT-**A00 type</p>  <p>MQT-**A03 type</p>   <p>MQT-**A05 type</p> 	<ul style="list-style-type: none"> • High speed precision QM Max. • High efficient finishing on tapered walls with 3-axis machines. • Precision finishing with XPHW/XPHT inserts. • Available sizes: 16mm dia. with 0°, 3° and 5° 20mm dia. with 0°, 3° and 5° 25mm dia. with 0° 35mm dia. with 0°
<p>FJVA type</p>  	<ul style="list-style-type: none"> • Highly accurate tool with specialized shape. Suitable for machining turbine blades. • Available sizes: 6mm, 8mm, 10mm & 12mm



Recommended cutting conditions:



STLP
TYPE

Solid modular head STLP type


- 4 flutes / Helix angle 30°



CATALOG NUMBER	STK	GRADE	No. of Flutes	DIMENSIONS (mm)										
				ϕDc	ℓ	Lf	BR	r ₁	r ₂	θ°	ϕDb	MD	C	W
STLP-4160T20R4-M8	•	DH115	4	16	17.7	26	1,500	4	4	20°	15	M8	5.5	14
STLP-4200T15R4-M10	•			20	30	38	1,500	4	5	15°	19	M10	5.5	17
STLP-4200T20R5-M10	•			20	22	30	1,500	5	5	20°	19	M10	5.5	17
STLP-4250T20R5-M12	•			25	28	38	2,200	5	5	20°	24	M12	5.5	22


Note: Be sure to use DIJET DS type spanner wrench to prevent over-tightening.

Example Of Use



- Has a large R cutting edge on the outer periphery.
- Highly efficient machining of inclined surfaces.
- Used mainly in 5-axis machining centers. You use "CAM" must also have a barrel module.

Cutting Data



Overhang length: 106mm

Result

STLP achieved high efficient & precision machining, compared with ball nose end mill.

Work	Part Name	Test piece
	Material	1049 C50
	Hardness	--
Tool	Tool No.	STLP4160T20R4-M8
	Grade	DH115
Cutting Conditions	n	n=10,000min ⁻¹
	Vf	Vf=1,200mm/min
	ap(mm)	2mm
	ae(mm)	0.15mm
	Coolant	Dry
	Machine	5-Axis MC

Recommended cutting conditions:




FJVA
TYPE

“FUJI BARRELL” FJVA type

- 4 flutes
- For shrink fit holder

Radius form accuracy on the outer periphery
±0.010mm



CATALOG NUMBER	STK	GRADE	No. of Flutes	DIMENSIONS (mm)						
				ØDc	BR	r1	r2	θ°	L	ØDs
FJVA4060S06-R250	•	DH115	4	6	250	1	1	25°	60	6
FJVA4080S08-R250	•			8	250	1	1.20	25°	75	8
FJVA4100S10-R250	•			10	250	1	1.75	25°	80	10
FJVA4120S12-R250	•			12	250	1	1.75	25°	100	12

Example Of Use

- Highly efficient machining of inclined surfaces.
- Used mainly in 5-axis machining centers.
- You use “CAM” must also have a barrel module.

Projection can be shortened, resulting in improved surface quality.



HEADQUARTER

DIJET Industrial Co.Ltd.
2-1-18, Kami-Higashi,
Hirano-ku, Osaka 547-0002, Japan
Phone: +81-6-6791-6781
Fax: +81-6-6793-1221
www.dijet.co.jp

MAIN OFFICE EUROPE

DIJET GmbH
Immemannstraße 9
40210 Düsseldorf, Germany
Phone: +49-211-50088820
Fax: +49-211-50088823
www.dijet.de



DIJET EUROPE



Web : www.dijet.de

